

| T3xm Treadmill



CONSOLE	
CSAFE READY-FITLINXX CERTIFIED	No
PRO:IDIOM COMPATIBLE	No
DISPLAY TYPE	Dot-matrix LED with profile display
WEB CONNECTIVITY	No
MULTIMEDIA PLAYBACK	No
USB PORT	Yes
BLUETOOTH ENABLED	No
IPTV COMPATIBLE	No
VIRTUAL ACTIVE COMPATIBLE	No
RFID COMPATIBLE	No
READING RACK	No
SECONDARY DATA DISPLAY	No
INTEGRATED VISTA CLEAR TELEVISION TECHNOLOGY	No
FITTOUCH TECHNOLOGY	No
PERSONAL TRAINER PORTAL COMPATIBLE	No
PERSONAL FAN	No
WORKOUTS	Manual, Rolling Hills, Fat Burn, 5k, 10k, Target HR, Gerkin Protocol, Army PFT, Navy PRT, Marine PFT, Air Force PRT, Physical Efficiency Battery (PEB), WFI Protocol
USER-DEFINED MULTI-LANGUAGE DISPLAY	Accessible only through manager menu: English, German, French, Italian, Spanish, Dutch, Portuguese, Japanese, Swedish, Finnish, Turkish, Polish, Russian, Danish

WIFI ENABLED	Optional
FACILITY COMMUNICATION PORTAL/CALENDAR	No
DISPLAY FEEDBACK	Time of Day, Time Elapsed, Time Remaining, Distance (Kilometers or Miles), Calories, Calories per Hour, Speed, Incline, Pace, Average Pace, Heart Rate, METs, Watts, Workout Profile, Forward/Reverse
ONE-BUTTON START	Yes
PAUSE FUNCTION	Yes
IPOD / IPHONE COMPATIBLE	Charging only
FITCONNEXION READY	No
WORKOUT TRACKING NETWORK COMPATIBLE	No
ASSET MANAGEMENT COMPATIBLE	Yes
ON-THE-FLY PROGRAM CHANGE	Yes
DRIVE SYSTEM	
DRIVE SYSTEM	Matrix 4.2 hp AC Dynamic Response Drive System with .1mA current leakage

FEATURES	
STEP-ON HEIGHT	19 cm / 7.5"
CONTACT & TELEMETRIC HR	Yes
INCLINE RANGE	0-15% (590-kg / 1,300-lb. thrust elevation motor)
TREAD SENSE	Yes. Engages above 0.8 kph / 0.5 mph
BELT TYPE	Habasit, 2-ply commercial grade
SPEED RANGE	0.16 – 19.3 km/h / 0.1 – 12 mph forward / 0.16 - 6.4 km/h 0.1 - 4 mph reverse
CROSSBAR CONTROLS	No
CUSHION SYSTEM	Ultimate Deck cushioning system
DECK TYPE	Ultimate hard-wax reversible 1" deck
RUNNING AREA	152 x 51 cm / 60" x 20"

TECH SPECS	
ELECTRICAL RECEPTACLE & PLUG	NEMA 220v 6-20R
ASSEMBLED WEIGHT	172 kg / 378 lbs.
MAX USER WEIGHT	182 kg / 400 lbs.
POWER REQUIREMENTS	20-amp dedicated circuit required, non-looped grounded
SHIPPING WEIGHT	186 kg / 409 lbs.
ASSEMBLED DIMENSIONS	215 x 85 x 142 cm / 84.6" x 33.5" x 56"